









**USB 2.0** 



























## **Technical Specification**

ENGINE					
Technology		Electrophotographic			
Print Speed	A4	Up to 22 ppm			
First Print Time		Less than 10 sec			
Resolution	Windows® 2000 / XP /Vista / Server 2003	HQ1200 (2400 x 600) / 600 / 300dpi			
	Mac OSX® 10.2.4 or greater	HQ1200 (2,400 x 600) / 600 / 300dpi			
	Linux	600 / 300 dpi			
CONTROLLER					
Processor		181MHz			
Memory		8MB			
Interface	Standard	Full-Speed USB2.0			
Emulation		GDI			
SOFTWARE					
Printer Driver	For Windows®	GDI Driver for Windows® 2000 / XP / Vista / Server 2003			
	For Macintosh®	Brother Laser Driver for MacOS® X 10.2.4 or greater			
	For Linux	GDI Driver for Linux (Download from http://solutions.brother.com)			
Utilities	Interactive Help	Instructional movie for the solution when any error message appears on the Status Monitor			
CONTROL PANEL					
Display	LED	4 LED (Toner/Drum/Error/Go)			
Buttons	1 button	Go			
PAPER HANDLING					
Paper Input	Manual Feed Slot	1 Sheet			
	Paper Tray (Standard)	Up to 250 Sheets <sup>^</sup> can be stored in the paper tray			
Paper Output	Face Down	Up to 100 Sheets^ can be stored in the output tray face down			
Duplex	Manual Duplex	Yes			
MEDIA SPECIF					
Media Types	Manual Feed Slot	Plain Paper, Bond Paper, Recycled Paper, Envelopes, Labels, and Transparencies			
	Paper Tray	Plain Paper, Bond Paper, Recycled Paper, Transparencies (up to 10 sheets^)			
Media Weights	Manual Feed Slot Paper Tray	60 - 163 gsm 60 - 105 gsm			
Media Sizes	Manual Feed Slot	Width 76.2 to 220 mm, Length 116 to 406.4 mm			
	Paper Tray	A4, Letter, B5(JIS, ISO), A5, B6, A6, Exe, Legal, Folio			
PRINTER DRIVER FUNCTIONS					
Page Layout	N in 1 Printing	Condense 2, 4, 9, 16 or 25 pages into 1 page			
	Poster Printing	Enlarge 1 page to print over 4, 9, 16 or 25 pages			
	Watermark Printing	Watermark documents with predefined text or			

Others	Quick Print Setup	A printer driver function that enables you to change the driver setting without opening the property dialog		
	Status Monitor	A function to indicate the printer error on the PC		
SUPPLIES				
<b>Toner Standard Yield</b>	I TN-2130	Up to 1,500 A4 pages in accordance with ISO/IEC19752		
Toner High Yield	TN-2150	Up to 2,600 A4 pages in accordance with ISO/IEC19752		
Drum	DR-2125	Up to 12,000 A4 pages (1 page / job)		
<b>DIMENSION/WI</b>	EIGHT			
Dimensions (WxDxH)		368 x 361 x 170.5 mm		
Weight		5.8kg		
OTHERS				
Power Consumption	Printing	Average 460W		
	Standby	Average 80W		
	Sleep	Average 5W		
Noise Level	Sound Pressure	Printing	51dB(A) or less	
		Standby	30dB(A) or less	
	Sound Power	Printing	6.7B(A) or less	
		Standby	4.5B(A) or less	
Ecology	Power Saving	Yes		
	Toner Saving	Yes		

The HL-2140 comes supplied with a Standard Yield Toner (TN-2130) and Drum (DR-2125)



Brother strongly recommends that our customers use genuine Brother consumable products only. The benefits to you are:

Better quality prints

Better quainty prints
Greater yields per consumable
You protect your machine from damages
Achieve optimum performance.
Failure to use only genuine Brother\* supplies may damage the machine and such damages may not be covered under warranty





HL-2140	Operating	Processor	Minimum	Recommended	Available Hard
	System Version	Speed	RAM	RAM	Disk Space
Windows	2000 Professional	Pentium 133MHz	64MB	256MB	50MB
	XΡ	Pentium 300MHZ	128MB	256MB	50MB
	2003 Server	Pentium 150MHz	256MB	512MB	50MB
	Vista	Pentium 300MHZ	512MB	1GB	50MB
Macintosh	OSX 10.2.4 or greater	minimum requirements	128MB	160MB	80MB

user defined messages



Contact:



## **Brother International (Aust) Pty Ltd**

Web-site: www.brother.com.au Technical Help Web-site: http://solutions.brother.com NSW/ACT 11 Talavera Road. Macquarie Park NSW 2113 Phone: (02) 9887 4344 Fax: (02) 9870 7234 VIC 1/733 Whitehorse Rd. Mont Albert VIC 3127 Phone: (03) 9899 4844 Fax: (03) 9899 4833 **QLD/NT** 245 Riverside Drive. West End QLD 4101 Phone: (07) 3255 1211 Fax: (07) 3255 1911 **SA/TAS** Unit 4, 13 King William Rd. Unley SA 5061 Phone: (08) 8272 1300 Fax: (08) 8272 1199 **WA** 117 Great Eastern Highway. Belmont WA 6104 Phone: (08) 9478 1955 Fax: (08) 9277 2177

All specifications subject to change without notice Brand product names are registered trademarks or trademarks of their respective companies